

BSO-45 is a lubricant preparation and is especially developed for processes that require both cooling and heating. It is also recommended for use in food processing plants. This fluid meets the requirement established by the FDA at 21 CFR 178.3620(b).

- This fluid is approved for food or pharmaceutical applications
- FDA approvals 21CFR 178.3620(b)


SPECIFICATIONS

OPERATING TEMPERATURE	DESIGN TEMPERATURE	FREEZING POINT TEMPERATURE
-40/+250 °C	+250°C	-48°C
TYPE	VISCOSITY	DENSITY
Hydrogenerated mineral oil	9.8 cSt	0.82 kg/dm ³

Note: viscosity and density at 25°C

VAPOUR PRESSURE RESULTS

BSO-45





Holland – United Kingdom – Romania – India – Thailand – Dubai – USA

To our knowledge, the information contained herein is accurate as of the date of this document. However neither Badotherm, nor its affiliates makes any warranty, express or limited, or accepts any liability in connection with this information or its use. This information is for technical skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other product. The user alone finally determines suitability of any information or material in contemplated use, the manner of use and whether any patents are infringed. This information gives typical properties only.

Badotherm reserves the right to make changes to the specifications and materials without prior notice. The latest version of the datasheet can be found on www.badotherm.com.

© 2001 Badotherm, all rights reserved. Trademarks and/or other products referenced herein are either trademarks or registered trademarks of Badotherm.